



ROADALTON

TRUCK AND BUS TYRE CATALOGUE



2025



ROADALT N



RA361

RF218

RF281

RF311

RD570

RD836

2025

RF311

Long haul



Steer, trailer



Paved road



Highway



CHARACTERISTICS

- ★ Excellent handling performance
- ★ Long tire service life
- ★ Low noise

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
315/80R22.5	22PR	312	1076	158/156	4250/4000	900/900	L	9.00	16.5

RD570

Long haul



Drive



Paved road



Highway



CHARACTERISTICS

- ★ Anti-wear
- ★ Excellent grip
- ★ Strong traction
- ★ High durability

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
315/80R22.5	22PR	312	1076	158/156	4250/4000	900/900	L	9.00	23

RA361

Medium and long haul



All position



CHARACTERISTICS

- ★ Strong traction
- ★ Fuel-economy
- ★ Long tire service life

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE (kpa)	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
385/65R22.5	24PR	389	1072	164	5000	900	K	11.75	16

RF218

Long haul



Steer,Trailer



CHARACTERISTICS

- ★ Anti-irregular wear
- ★ Low noise
- ★ Fuel-economy
- ★ Excellent self-cleaning

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX	MAX LOAD (kg)	PRESSURE (kpa)	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
385/65R22.5	24PR	389	1072	164	5000	900	K	11.75	17

RF281

Regional & Medium



All position



CHARACTERISTICS

- ★ Fuel-economy
- ★ Anti wear
- ★ Excellent handing performance
- ★ Low noise

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
235/75R17.5	18PR	233	797	143/141	2725/2575	875/875	J	6.75	13.5

RD836



E-4

CHARACTERISTICS

- ★ Strong traction
- ★ Cut & chip resistance
- ★ High load capacity



SIZE	STAR RATING	TYPE	TRA CODE	STANDARD RIM	TREAD DEPTH (mm)	LOAD INDEX	SECTION WIDTH (mm)	OVERALL DIAMETER (mm)	MAX LOAD AND INFLATION PRESSURE (kg/kpa) TRA	
									50KM/H	10KM/H
12.00R24	★★★	TT	E-4	8.5	31.5	164/162B	315	1245	5000/900 (single 50km/h) 4750/900(dual 50km/h)	
12.00R24	★★★	TT	E-4	8.5	31.5	164/162E	315	1245	5000/900 (single 70km/h) 4750/900(dual 70km/h)	
12.00R24	★★★	TT	E-4	8.5	31.5	164/162F	315	1245	5000/900 (single 80km/h) 4750/900(dual 80km/h)	
18.00R33	★★	TL	E-4	13.00/2.5	54	191B/209A2	500	1875	10900/700	
21.00R33	★★	TT/TL	E-4	15.00/3.0	54	200B	570	1955	14000/650	
24.00R35	★★	TL	E-4	17.00/3.5	63	209B/227A2	655	2175	18500/700	
24.00R35	★★★	TL	E-4	17.00/3.5	63	214B	655	2175	21200/900	

RF811

Regional & Medium



All position



City Road



CHARACTERISTICS

- ★ Anti-eccentric wear
- ★ Fuel-economy
- ★ Cost-effective

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
275/70R22.5	16PR		958	148/145	3150/2900	900/900	M	8.25	19.2
275/70R22.5	18PR		958	148/145	3150/2900	900/900	J	8.25	19.2

RA111

Regional & Medium



All position



Paved road



Highway



CHARACTERISTICS

- ★ Fuel-economy
- ★ Cost-effective

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	K	6.00G	12

RA116

Regional & Medium



All position



Paved road



Highway



CHARACTERISTICS

★ Fuel-economy

★ Cost-effective

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
7.00R16LT	14PR	200	775	118/114	1320/1180	770/770	L	5.50F	10

RF216

Regional & Medium



All position



Paved road



Highway



CHARACTERISTICS

★ Fuel-economy

★ Cost-effective

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
7.50R16LT	16PR	215	805	124/120	1600/1405	800/800	K	6.00G	11
8.25R16LT	16PR	235	855	128/124	1800/1600	770/770	K	6.50H	12

RA 168

Regional & Medium



All position



CHARACTERISTICS

- ★ Low fault rate
- ★ Cost-effective

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
325/95R24	22PR	325	1228	162/160	4750/4500	850/850	K	9.0	17

RA 166

Regional & Medium



All position



CHARACTERISTICS

- ★ Cost-effective
- ★ Low fault rate

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
325/95R24	22PR	325	1228	162/160	4750/4500	850/850	K	9.0	17.5

RD217

Medium and long haul



Drive



Paved road



Highway



CHARACTERISTICS

- ★ Excellent heat dispersion performance
- ★ Strong traction
- ★ Excellent wet grip performance

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
11R22.5	16PR	279	1050	148/145	3150/2900	850/850	M	8.25	20
295/80R22.5	18PR	298	1044	152/149	3550/3250	900/900	M	9.00	20.5
315/70R22.5	18PR	312	1014	154/150	3750/3350	900/900	M	9.00	19
315/80R22.5	20PR	312	1076	156/150	4000/3350	850/850	L	9.00	21

RA211

Medium and long haul



Steer, trailer



Paved road



Highway



CHARACTERISTICS

- ★ Cost-effective
- ★ Low fault rate

SIZE	PR	NEW TYRE INFLATED DIMENSIONS(mm)		LOAD INDEX SINGLE/DUAL	MAX LOAD (kg) SINGLE/DUAL	PRESSURE (kpa) SINGLE/DUAL	SPEED RATING	STANDARD RIM	TREAD DEPTH (mm)
		SECTION WIDTH	OVERALL DIAMETER						
275/70R22.5	16PR	276	958	148/145	3150/2900	900/900	M	8.25	14.8
315/70R22.5	18PR	312	1014	154/150	3750/3350	900/900	M	9.00	15



ROAD ALTON

SAMAA AL MADINA TYRE TRADING L.L.C

Address: No. 33 (Samaa Al Madina), Al Maktoum St., Deira, Dubai, UAE

MOB:+971 50 822 4063

TEL-FAX:+971 4 259 6560

P.O.Box:384823,dubai-U.A.E

Email:D.dgt@yahoo.com

www.samaatyre.com

